

## "HOW TO ORDER DOCUMENT"

	SHELL SIZE	Α	В	ØС	ØD	E	F	
		THREAD-2B (in Inches)	dia max	dia max	dia min	+13.0	max	
						-7.0		
	9	0.6250-0.1P-0.3L-TS	23	27	17.64	127	23	
	11	0.7500-0.1P-0.3L-TS	32	32	21.97	127	23	
4	13	0.8750-0.1P-0.3L-TS	37	37	25.12	127	23	
	15	1.0000-0.1P-0.3L-TS	40	40	29.92	127	23	
	17	1.1875-0.1P-0.3L-TS	44	44	32	127	23	
	19	1.2500-0.1P-0.3L-TS	46	46	36.27	127	23	
	21	1.3750-0.1P-0.3L-TS	49	49	38.25	127	23	
	23	1.5000-0.1P-0.3L-TS	54	54	42.62	127	23	_
	25	1.6250-0.1P-0.3L-TS	56	56	44.45	127	23	

NOTE:
1) "E" DISTANCE WILL BE FROM CENTER-TO-CENTER OF LUG HOLE

2) ROPE HAVE FREE ROTATION ON FASTENER 3) ALL COMPONENTS ARE COMPLIANCE TO THE MIL-DTL-38999/33

						ONTH.WILLIMIETER	1
PECIFICATION REQUIREMENTS				DRAWN	RHK	This document is the property of M/s. Ampm	
					CHECKED	RPT	Interconnect (P) Ltd., Rights of reproduction,
Α		INITIAL RELEASE			APR'VD		utilization or disclosure to the third parties in any
REV	ECN NO.	DESCRIPTION	DATE	APR'VD	DATE	15-05-2024	form whatsoever, is not allowed without the
REVISIONS DETAILS					SCALE - NTS		written consent of the

THIRD ANGLE PROJECTION

	SPECIFICATION					
NO.	PART NAME	MATERIAL	FINISH			
01	SHELL	ALUMINIUM	AS PER ORDER			
02	FASTENERS	STAINLESS STEEL	PASSIVATED			
03	RING	STAINLESS STEEL	PASSIVATED			
04	CHAIN	STAINLESS STEEL	PASSIVATED			
05	GASKET	SILICON ELASTOMER	NATURAL			
06	INSULATED ROPE	7STRAND STAINLESS STEEL	PASSIVATED			
07	IUG	STAINLESS STEEL	PASSIVATED			

UNSPECIFIED	
TOLERANCE	
. X ± 0.38	
. XX ± 0.25	
ANGLE ± 1°	<i></i>
	PELIARIE CONNECTOR SOLUTIONS

INDUSTRIAL TOWN, BANGALORE, INDIA - 560010 PH:+91 6363911299 sales@ampmil.com

This document is the property of M/s. Ampmil Interconnect (P) Ltd., Rights of reproduction, MIL-DTL-38999 SERIES III PROTECTIVE COVER FOR RECEPTACLE utilization or disclosure

PART NUMBER AP38999/33XXX (FOR XXX CONFIGURATION REFER HOW TO ORDER DOCUMENT)